

IN THE CLAIMS

Please amend the claims as follows:

1. (Currently Amended) An arrangement station for reproducing a multimedia signal, the arrangement comprising:es
_____ presenting means for presenting the multimedia signal to a user; ~~wherein the arrangement station comprises~~
_____ delay determining means for determining a packet delay measure representing the arrival delay of packets carrying the multimedia signal, and
_____ wherein the presenting means includes ~~comprises control~~ means ~~having a~~ comparison means for determining a difference signalvalue ~~representing a difference between the~~ packet delay measure and a reference value, and ~~in that the presentation means comprises an~~ adjusting means for adjusting the presenting speed in dependence on the difference signalvalue.
2. (Previously Amended) The arrangement according to claim 1, wherein the multimedia signal comprises an audio signal, and in that the presenting means are arranged for varying the presenting speed of the audio signal without substantially changing a perceived intonation of the audio signal.
3. (Currently Amended) The arrangement according to claim 2, wherein the audio signal is represented by a plurality of segments comprising a plurality of signals being described by at least their amplitude and frequency, and in that the presenting means are arranged for changing the duration of said segments in dependence on said packet delay ~~measure~~.
4. (Cancelled)

5. (Previously Amended) The arrangement according to claim 1, wherein the presentation means comprises adaptation means for adapting the reference value in dependence on the variations of the difference value.

6. (Previously Amended) The arrangement according to claim 1, wherein the multimedia signal comprises a video signal.

7. (Previously Amended) The arrangement according to claim 6, wherein the video signal is represented by a at least one object, and in that the presentation means are arranged for varying the presentation speed by adjusting a movement speed of at least one object in the video signal.

8. (Cancelled)

9. (Currently Amended) A method for reproducing a multimedia signal, said method comprises presenting the multimedia signal to a user, determining a packet delay measure representing an arrival delay of packets carrying the multimedia signal, and determining a difference signal value representing a difference between the packet delay measure and a reference value, and adjusting the presenting speed in dependence on the difference value~~signal~~.

10. (Previously Amended) The method according to claim 9, wherein the multimedia signal comprises an audio signal, and in that the method comprises varying the presenting speed of the audio signal without substantially changing a perceived intonation of the audio signal.

11. (Currently Amended) The method according to claim 10, wherein the audio signal is represented by a plurality of segments comprising a plurality of waveforms being described by at least their amplitude and frequency, and in that the method comprises changing the duration of said segments in dependence on said packet delay measure.

12. (Previously Amended) The method according to claim 9, wherein the multimedia signal comprises a video signal.

13. (Previously Amended) The method according to claim 12, wherein the video signal is represented by at least one object, and in that the method comprises varying the presentation speed by adjusting a movement speed of at least one object in the video signal.

14. (Previously Added) The arrangement according to claim 1, wherein the delay determining means measures a delay of the packets by comparing timestamps of the multimedia signal.

15. (Previously Added) The arrangement according to claim 1, wherein the delay determining means measures a delay of the packets based on the number of packets present in a buffer with a reference value REF.

16. (Previously Added) The arrangement according to claim 1, wherein the presenting means varies the presentation speed within 240% without substantially changing the intonation of an audio signal component of the multimedia signal.

17. (Previously Added) The method according to claim 11, further including the step of adapting the reference value in dependence on the variations of the difference value signal.

18. (New) An arrangement station for reproducing a multimedia signal, the arrangement comprising:

a processor configured to present the multimedia signal to a user; determine a packet delay representing the arrival delay of packets carrying the multimedia signal, and determine a difference value between the packet delay and a reference value, and adjust the presenting speed in dependence on the difference value.